



304 Smokey Lane North Little Rock, Arkansas 72117 Phone: (501) 945-0354 FAX: (501) 945-0370  
www.StreetandPerformanceElectronics.com

## *Helix Power Tower PLUS* Installation Instructions

(2004-2006 GM Canyon/Colorado 3.5L I-5  
2006 HUMMER H3 3.5L I-5 Part #35105)

### **Important! Read all instructions before you begin installation.**

1. Disconnect atmospheric vent hose from the air cleaner resonator. Loosen the air cleaner resonator outlet duct clamp Remove the 2 air cleaner resonator bolts. Complete the following in order to remove the air cleaner resonator and outlet duct from the engine:
  - A. Lift upward on the assembly.
  - B. Disconnect the following: The crankcase ventilation hose from the camshaft cover and the outlet duct from the throttle body.
  - C. Remove the assembly from the engine.
2. Loosen and remove four throttle body nuts/studs. (Note: a 4mm 6-point socket works well)
3. Install the Helix Power Tower PLUS between the intake manifold and throttle body assembly (engraving facing the throttle body). Now slip the supplied gasket in between the Power Tower PLUS and throttle body assembly. Fasten the throttle body with the supplied longer bolts and washers. Tighten the bolts to 89 lb/in.
4. Complete the following in order to install the air cleaner resonator and outlet duct to the engine:
  - A. Position the outlet duct over the throttle body assembly.
  - B. Install the crankcase ventilation hose to the camshaft cover port.
  - C. Align the air cleaner outlet resonator bolt with the captured nuts on the camshaft cover.
5. Position the air cleaner resonator outlet duct clamp. Tighten the air cleaner resonator outlet duct clamp.
6. Install the 2-air cleaner outlet resonator to camshaft cover bolts. Tighten bolts to (53 lb/in).
7. Connect the atmospheric vent hose to the air cleaner resonator.

#### **Parts List**

1 Helix Power Tower PLUS  
1 Gasket  
4 6mm x 65mm bolts  
4 6mm flat washers