



Street & Performance Electronics
304 Smokey Lane
North Little Rock, Arkansas 72117
Phone: (501) 945-0354 FAX: (501) 945-0370
www.StreetandPerformanceElectronics.com

Helix Power Tower PLUS

Throttle Body Spacer
Installation Instructions

(2009 Dodge RAM 1500/3500 5.7L Part #57049)

Important!

**Read all instructions
before you begin
installation.**

Important! Read all instructions before you begin installation.

1. Disconnect Air Intake Temperature (IAT) sensor harness from sensor located on air inlet tube. Loosen and remove air inlet tube from air filter assembly to throttle body.
2. Loosen and remove engine sight cover, if equipped.
3. Loosen and remove four bolts securing the throttle body to the intake manifold.
4. Install throttle body spacer (engraved AIR IN facing up), new gasket and throttle body onto intake manifold using the supplied flat washers and longer bolts. Carefully tighten screws to secure throttle body (Torque to 48in/lb). Remember, this is a plastic manifold and does not require extreme torque. Do not strip these.

CAUTION: Over torque of the throttle body bolts can result in intake manifold damage. Street & Performance Electronics, Inc. will not be responsible for damage to the intake manifold due to over torque of the throttle body bolts.

5. Install engine sight cover, if equipped. Install air inlet tube. Tighten clamps on air inlet tube. Reconnect IAT harness to sensor.



Parts List

- 1 Helix Power Tower Plus
- 1 Gasket
- 4 6mm x 80mm screws
- 4 6mm flat washers