



304 Smokey Lane North Little Rock, Arkansas 72117 Phone: (501) 945-0354 FAX: (501) 945-0370
www.StreetandPerformanceElectronics.com

Helix Power Tower PLUS Installation Instructions

(2005-2006 Chevrolet SSR 6.0L (LS2)
2005-2006 Pontiac GTO 6.0L (LS2) Part #60025)

Important! Read all instructions before you begin installation.

1. Loosen and remove the air filter assembly from throttle body. Remove the air filter assembly from vehicle. If you have an aftermarket air intake you might have to remove it completely to access the throttle body.
2. Remove the TAC harness from throttle body. Loosen and remove the retaining bolts and nuts from throttle body. Remove the studs from the intake manifold using a 6-point 4mm socket.
3. Install the Helix Power Tower PLUS between the intake manifold and throttle body assembly (engraving facing the throttle body). Now slip the supplied gasket in between the Power Tower PLUS and throttle body assembly. Fasten the throttle body with the supplied longer bolts and washers. Tighten the bolts to 10 Nm (89 lb/in).
4. If using an aftermarket air intake you might have to trim the air inlet to accommodate the spacer the Helix Power Tower PLUS needs for installation.

2005-2005 SSR INSTALLATION PICTURES



2005-2006 GTO INSTALLATION PICTURES



Parts List

- 1 Helix Power Tower PLUS
- 1 Gasket
- 4 6mm x 65mm bolts
- 4 6mm lock washers
- 4 6mm flat washers