



304 Smokey Lane North Little Rock, Arkansas 72117 Phone: (501) 945-0354 FAX: (501) 945-0370
www.StreetandPerformanceElectronics.com

Helix Power Tower PLUS **Installation Instructions**

(1998-2001 Honda Accord 3.0L V-TEC Part #91003)

Important! Read all instructions before you begin installation.

1. Remove air inlet assembly from throttle body. Remove two linkage bolts. Remove 2 bolts and 2 nuts securing the throttle body to intake manifold. Remove the two studs from intake manifold.
2. Install a new gasket, Helix Power Tower PLUS (engraved side towards throttle body), and new gasket onto intake manifold. On some applications there is already a spacer, this is to be retained for the idle air control. Use the even longer bolts to secure the assembly (supplied in kit). Secure this assembly with the longer bolts and washers (supplied in kit) and torque to 15 ft/lb.
3. Reattach throttle linkage to intake manifold with two 25mm spacer and original bolts under each bolt location. Torque to 12 ft/lb. Install throttle extender bracket onto stock mounting position. Bolt original throttle bracket to the extender plate. Torque to 10 ft/lb.
4. Reinstall the air inlet assembly to throttle body. You may extra have extra mounting hardware.



Parts List

1 Helix Power Tower PLUS
2 Gaskets
4 8mmx60mm bolts
4 8mmx65mm bolts
4 8mm flat washers
2 25mm spacers

3 6mmx12mm bolts
2 6mmx25mm bolts
2 6mmx35mm bolts
2 6mm washers
1 Throttle extender bracket
1 6mm nut