



304 Smokey Lane North Little Rock, Arkansas 72117 Phone: (501) 945-0354 FAX: (501) 945-0370
www.StreetandPerformanceElectronics.com

Helix Power Tower PLUS **Installation Instructions**

(1995-1999 Mitsubishi Eclipse 2.4L Non-Turbo Part #93002)

Important! Read all instructions before you begin installation.

1. Unclamp and remove air inlet from throttle body. Unbolt throttle cable bracket from intake manifold.
2. Remove three bolts hold the stabilizer bracket on throttle body. Remove four bolts that secure throttle body to intake manifold.
3. Install new gasket, Helix Power Tower PLUS, another gasket and throttle body onto intake manifold using supplied longer bolts. Torque to 15 ft/lb. Install new stabilizer bracket to intake manifold with original bolts. Bolt throttle body to new stabilizer bracket.
4. Install throttle cable extender bracket to intake manifold. Use supplied longer bolts to secure assembly to mounting bracket. Torque to 12 ft/lb. Install air inlet assembly on the throttle body. Tighten clamp to throttle body.



Parts List

- 1 Helix Power Tower PLUS
- 2 Gaskets
- 4 8mmx75mm bolts
- 4 8mm flat washers
- 2 6mmx16mm bolts
- 2 6mm washers
- 2 6mm counter-sunk bolts
- 1 Throttle cable extender
- 1 Stabilizer bracket