



304 Smokey Lane North Little Rock, Arkansas 72117 Phone: (501) 945-0354 FAX: (501) 945-0370
www.StreetandPerformanceElectronics.com

Helix Power Tower Installation Instructions

(2004-2008 Nissan Armada 5.6L V-8
2004-2008 Nissan Titan 5.6L V-8 Part #94560)

Important! Read all instructions before you begin installation.

1. Unbolt and remove engine cover. Loosen and remove PCV vent hoses from air inlet tube. Loosen and remove air inlet tube from throttle body and air filter assembly. Remove engine cover bracket from intake manifold.
2. Loosen and remove the four socket cap bolts from the throttle body with a 5mm hex. Remove throttle body away from intake manifold.
3. Install the Helix Power Tower PLUS (engraved side towards throttle body) and a gasket onto the manifold with the longer bolts and washers (supplied in kit). Tighten the bolts to 10 Nm (89 lb/in).
4. Install air inlet tube onto the throttle body and air filter assembly. Reconnect the PCV vent hose to air inlet tube. Reattach the engine cover bracket to intake manifold. Reinstall the engine cover to bracket.



Parts List

- 1 Helix Power Tower Plus
- 1 Gasket
- 4 6mm x 70mm bolts
- 4 6mm flat washers
- 4 6mm lock washers