



304 Smokey Lane North Little Rock, Arkansas 72117 Phone: (501) 945-0354 FAX: (501) 945-0370
www.StreetandPerformanceElectronics.com

Helix Power Tower Installation Instructions

(2002-2004 Toyota Celica 1.8L DOHC (1ZZFE)
2000-2004 Toyota Corolla 1.8L DOHC (1ZZFE)
2003-2004 Toyota Matrix 1.8L DOHC (1ZZFE) Part #97185)

Important! Read all instructions before you begin installation.

1. Disconnect hose and electrical connections from air cleaner assembly. Remove air cleaner assembly from vehicle. Remove air inlet pipe from throttle body. **If you have an aftermarket air intake system, you may have to remove it completely to access the throttle body.**
2. Remove two nuts and two bolts that are holding the throttle body to the intake manifold.
3. Remove the two upper studs from the intake manifold, using a 5mm 6pt socket.
4. Install the Helix Power Tower Plus (engraved side towards the throttle body), gasket and throttle body onto the intake manifold. Use the supplied bolts and washers to secure the throttle body to the intake manifold. Torque to 12 lb/ft.
5. Install air cleaner assembly back into vehicle. **If you have an aftermarket air intake system, you may have to adjust or trim the intake system for the throttle body's new position.**
6. Reconnect air inlet pipe to throttle body. Install air cleaner assembly and reconnect electrical connections.



Parts List

- 1 Helix Power Tower Plus
- 1 Gasket
- 4 8mm x 75mm bolts
- 4 8mm washers